

Presque Isle Wine Cellars
9440 W. Main Rd
North East, PA 16428
814-725-1314 or 800-488-7492
info@piwine.com
www.piwine.com

O'Sullivan 5-964 Gondola Enamel

DESCRIPTION

A premium, heavy-duty coating combining the qualities of toughness and chemical resistance with the convenience of soap and water cleanup. Feature superior gloss and color retention, for outside use, it also has excellent mildew resistance.

USES

Steel gondolas, equipment, bottling room walls, conveyors, presses, tank pads, stemmer/crushers.

COVERAGE

400 square feet/gallon average per coat.
-or- 57 ft² per 500cc.

FINISH

Gloss.

COLORS

White, gray, yellow, tile red or black

DRYING

Set to touch 15-30 minutes, recoat 2-4 hours.
Allow 1 month to cure before using surface.

RECOMMENDED THINNER

Water.

SURFACE PREPARATION

Surface should be cleaned with soap and water and free of loose paint, etc. Since it contains non-toxic corrosive inhibitors, it can be self-priming. **Sand surface well for best adhesion.**

APPLICATION

Brush, roller, or spray (airless or conventional).

RESISTS

Wine acids, caustic, alcohol. Good toughness.

CAUTION

Industrial product. Keep out of reach of children. Do not apply when air temp is below 60F. Store in warm room. Do not spray in confined area without proper ventilation and respirator. This is an industrial product. Use in well ventilated area.

TEMPERATURE RATING

-20°F if surface is not flexible -and- up to 200°F.

TECHNICAL CONSULTANTS:

Varni-Lite Coatings (510) 887-8997

Varni-Lite coatings, Inc.
21595 Curtis Street
Hayward, Ca. 94545
(510)887-8997 Fax :(510)887-5637

Oct 13, 2015

To Whom It May Concern:

This is to certify that the ingredients in product # 5964 Aqualloy Enamel are listed in title 21 –code of federal regulations for food and drugs, section 175.300 section VIII (a – c), 177.1010, and 175,210 covering products for use on indirect contact with food.

Sincerely,

Bruce Sohrabi
21595 Curtis St.
Hayward, CA 94545
510-887-8997