

<u>info@piwine.com</u> 800-488-7492

O' Sullivan 5-X650 BarrelGuard - Mildewcide

USES:	Barrels, wood tanks, or any porous wood surface. Allows wood to breathe.
COLOR:	Milky green — dries to clear finish
COVERAGE:	200 square feet per gallon; Depends on porosity of surface; A 59 gallon barrel has 20.65 ft ²
FINISH:	Low satin sheen — multiple coats increase sheen
VISCOSITY:	Thin liquid
DRYING TIME:	24 hours
FLASH POINT:	N/A (5-X650 is a water-base emulsion)
THINNER:	None — wash equipment in warm soapy water
SURFACE PREPARATION:	A porous surface is required. Remove all old coatings with soda ash and hot water; or in difficult instances use Epoxy Remover and rinse with clean water. Wood barrels may be swollen before BarrelGuard is applied; however the surface should not be too wet or coating will not dry properly. Always kill mildew before coating. Use Sodium Hypochlorite solution (Clorox, etc.) rinsed with clean water.
APPLICATION:	Apply by means of brush, roller, or spray; apply full wet coats; Allow 24 hrs+ between coats.
RESISTS:	Mildew and discoloration.

CAUTION:

Do not apply when air temperature is below 60° F. Store in warm room. Do not spray in confined area without proper ventilation and respirator. This is an industrial product. Keep out of reach of children. Use in well ventilated area.

The information in this data sheet is to the best of our knowledge correct at the date of printing. The company reserves the right to modify data without notice. Any change in data will normally be followed by issue of a new data sheet. The user should check the date of printing and if more than 12 months have elapsed, then the data should only be used after checking with our nearest sales office to establish that they are still valid. Since condition of application and service may be beyond our control, no liability can be accepted based on these data. Dated 4/20/2022